

**RAFIX 22 FSR - Keylock switch, latching, 1 x 90°, V shape****1.30.285.321/0100****General information**

|                     |       |
|---------------------|-------|
| Color of front ring | black |
| Form of collar      | round |

**Dimensions**

|                      |            |
|----------------------|------------|
| Dimensions of collar | ø 31.3 mm  |
| Overall height       | 45.1 mm    |
| Mounting hole        | 22.3 mm    |
| Key grid             | 35 x 35 mm |

**Mechanical design**

|                      |                  |
|----------------------|------------------|
| Mounting             | ring nut         |
| Contact function     | latching         |
| Wafers               | 5                |
| Illuminability       | no               |
| Lock type            | 001              |
| Main key             | on request       |
| Rotating angle       | 1 x 90°, V shape |
| Key removal position | 0+1              |
| Torque for nut ring  | 1.2 Nm           |

**Mechanical characteristics**

|             |        |
|-------------|--------|
| Torque max. | 1.3 Nm |
|-------------|--------|

**Other specifications**

|                                      |   |
|--------------------------------------|---|
| Degree of protection from front side | IP65 (DIN EN 60529); IP69K (ISO 20653) water temp. 23 °C<br>+3 °C |
| Ambient temp. operating min.         | -40 °C  |
| Ambient temp. operating max.         | +85 °C  |
| Storage temperature min.             | -40 °C  |
| Storage temperature max.             | +85 °C  |
| Environmental resistance             | acc. to IEC 60068-2-14, -30, -33 and -78                          |
| Salt spray                           | IEC 600 68-2-11   |
| ROHS compliant                       | yes   |
| REACH compliant                      | yes   |

---

Panel cut-out to IEC 60947-5-1

