# Wipe-key Keyboard J84-4300



This Slim, low profile, compact keyboard with integrated pointing device offers an IP55 rating for protection against dust and spraying liquids. It's ideal for applications requiring frequent disinfection for elimination of germs. Uses include diagnostics equipment, medical carts, rack mount servers, laboratories, and kiosks.



## **Facts & Features**

- Membrane technology provides dust, dirt, and spraying water protection.
- Designed for continuous use more than 10 Million key operations
- High reliability and uniquely precise tactile keying
- Full 87 US key layout
- Ultra slim overall height only 19 mm
- Uses Standard Operating System Drivers
- Ideal for use with space limitations

#### **Technical Data**

- Interface USB
- Cable Length approx. 1.62 m
- Keyswitch Lifetime

Key life: 10 Million operations

# **Technical Data**

<u>Layout</u>
 87 US key layout

Weight

Without Packaging 600 +/- 20 g 1.3 lbs With Packaging730 g (Approx) 1.6 lbs

Dimensions

Keyboard: 370 x 139 x 19 mm 14.5" x 5.5" x .75" Packaging: 396 x 210 x 43 mm 15.6" x 8.3" x 1.7"

- Current Consumption 40mA (MAX)
- Humidity 0~95% RH
- Operating Temperature 0°C to +60°C



## **Technical Data**

- Storage / Transport Temperature
  -20°C to +60°C
- Packaging Unit
  20 keyboards per master carton
  12 master cartons per pallet (252 pcs.)
- Warranty2 years

## **System Requirements**

USB Port & supporting operating system

#### **Delivery Volume**

Keyboard, Manual

#### **Compatible Operating Systems**

Win 98SE, ME, 2000, XP, XP x 64, Vista, Windows 7

## **Agency Approvals / Instructions**

■ CE, FCC Class B, BSMI, RoHS

# Order Description

Order Number	Interface	Color
J84-4300LUAUS-2	USB	Black

Other country versions available upon request. (Special conditions apply)

ZF Electronic Systems Pleasant Prairie, LLC 11200 88th Avenue Pleasant Prairie, WI 53158

**USA** 

Phone: 262.942.6500

Internet: www.cherrycorp.com

Sales: 262.942.6562

E-Mail: CEP\_sales@ZF.com

Fax: 262.942.6566

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2013 ZF Electronic Systems Pleasant Prairie, LLC Last update: February 5, 2013