

## Fabric label sheet - BMK 20X 8 WH - 0805470

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fabric label sheet, Sheet, white, unlabeled, can be labeled with: Plotter, Mounting type: Adhesive, Lettering field: 20 mm x 8 mm

The illustration shows version BMK 38x11 in yellow

### Product Features

- Available in various dimensions
- Self-adhesive labels for labeling by hand or with a plotter
- Labeling service: Phoenix Contact can custom-label all BMK ... markers according to your requirements
- Secure adhesion even on curved or uneven surfaces as well as round corners
- The material file can be downloaded under the CLIP PROJECT software under Downloads - "Software update - Marking".

### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	19.32 g
Custom tariff number	39199000
Country of origin	Belgium

### Technical data

#### Dimensions

Length (b)	20 mm
Width (a)	8 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
---------------------------------	------------------

#### General

Note	Can be labeled with CMS
Color	white
Base element material	Polyester foil
Components	Silicone-free

## Fabric label sheet - BMK 20X 8 WH - 0805470

### Technical data

#### General

Flammability rating according to UL 94	V0
Material	Polyester foil
Number of individual labels	270
Number of individual labels per row	9
Adhesive	Acrylic
Printability	Plotter
Device	5144615 CMS-P1-PLOTTER
Test for substances that would hinder coating with paint or varnish	VW PV 3.10.7:2005-02
Result	Test passed
Test specification weathering-resistance	Following ISO 4892-2:2013-03
Test duration	96 h
Wipe resistance test result	Test passed
Salt spray test specification	DIN EN 60068-2-11:2000-02
Test duration	96 h
Salt spray testing result	Test passed
Alternating condensation climate with SO2 test specification	DIN 50018:2013-05
Climate level	AHT 1.0 S
Cycles	2
Condensation test result	Test passed
Wipe resistance of test specification inscriptions	DIN EN 61010-1 (VDE 0411-1):2011-07
Result	Test passed
Marking mounting type	Adhesive

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

### Classifications

#### eCl@ss

eCl@ss 4.0	24190218
eCl@ss 4.1	24190218
eCl@ss 5.0	27141137
eCl@ss 5.1	27141137
eCl@ss 6.0	27141137
eCl@ss 7.0	27141137
eCl@ss 8.0	27149129

## Fabric label sheet - BMK 20X 8 WH - 0805470

### Classifications

#### ETIM

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC000761
ETIM 5.0	EC001288

#### UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410